

MV-VC114-5032G is a Voltage Controlled Crystal Oscillator (VCXO) . This VCXO provide good phase noise and jitter performance over a wide operating temperature range, CMOS output and comes in a Hermetic Ceramic 5.0x3.2mm package. This device contains an internal voltage regulator resulting in excellent power supply rejection ratio.

The device is qualified to meet the JEDEC standard for Pb-Free assembly and compliant to the RoHS directive.

Electrical Performance

Parameter	Min	Typ	Max	Units
General				
Output Frequency	1		80	MHz
Operating Temperature	-10/+70 -40/+85 -40/+105 -40/+125			°C
Stability Over Temperature	±50 ±25 ±20			ppm
Start Up Time			10	ms
Package Size	5.0 x 3.2 x 1.3			mm
Supply				
Supply Voltage (Vdd)	4.75	5	5.25	V
Supply Current		5	9	mA
Current, Output Disabled		1	2	mA
Tuning				
Absolute Pull Range		±50		ppm
Control Voltage to reach Pull Range	0		Vdd + 0.5	V
Control Voltage Impedance	100			KΩ
Control Voltage Modulation BW	15			kHz
Output				
Output Signal		CMOS		
Output Logic Level				
Output Level - Logic High	Vdd-0.4			V
Output Level - Logic Low			0.4	V
Output Load		15 pF		
Output Rise and Fall Time		3.0	4.5	ns
Duty Cycle	40		60	%
Enable / Disable				
Output Enable / Disable				
Output Enabled	Vdd x 0.7			V
Output Disabled			Vdd x 0.3	V
Phase Noise & Jitter				
Phase Noise: (61.44 MHz)				
10 Hz offset		-63		dBc/Hz
100 Hz offset		-97		dBc/Hz
1kHz offset		-129		dBc/Hz
10kHz offset		-144		dBc/Hz
100kHz offset		-157		dBc/Hz
1MHz offset		-159		dBc/Hz
10MHz offset		-164		dBc/Hz
Jitter				
RMS Jitter: (12kHz - 20MHz) - 61.44 MHz		0.12		ps

Notes:

- 1 Pull Range tested with Vc = 0V to 3.0V
- 2 Rise and Fall times measured from 20% to 80% of a full output swing
- 3 Power Supply pin should be filtered. e.g. 0.1µF or 0.01 µF Capacitor for optimal performance.
- 4 The Output is Enabled if the Enable/Disable is left open.

Maximum Ratings



Storage Temp	-55°C to 125°C
Supply Voltage	-0.5V to +7.0V
Control Voltage	-0.5V to Vdd+0.5V
Enable/Disable Voltage	-0.5V to Vdd+0.5V
Junction Temperature	+150 °C

Maximum Ratings Notes:

- 1 Stresses in excess of the absolute maximum ratings can permanently damage the device.
- 2 Exposure to absolute maximum ratings for extended periods may adversely affect device reliability.

Package Information

Pin #	Function
Pin 1	Vc = Control Voltage or NC
Pin 2	E/D = Enable / Disable or NC
Pin 3	GND = Ground
Pin 4	OUT = Output
Pin 5	E/D = Enable / Disable
Pin 6	Vdd = Supply Voltage

Pad Layout

Package Outline Drawing
Handling and Construction

Package Construction	Hermetic Ceramic
Contact Pads	Gold over Nickle
Moisture Sensivity Level	MSL 1
ESD, Human Body Model	500V
ESD, Charge Device Model	500V

Ordering Information

MV-VC114-5032G - A x x C x - xxMxxxxx



① Voltage

A: 5 V

② Temp Range

J: -10/+70 °C

K: -40/+85 °C

L: -40/+105 °C

③ Temp Stability

C: ±50 ppm

E: ±25 ppm

F: ±20 ppm

④ Absolute Pull Range ⑤ Enable

C: ±50 ppm

2: Enable on Pin 2

5: Enable on Pin 5