

MV-VC115-5032G is a Voltage Controlled Crystal Oscillator (VCXO) . This VCXO provide good phase noise and jitter performance over a wide operating temperature range, CMOS output and comes in a Hermetic Ceramic 5.0x3.2mm package. This device contains an internal voltage regulator resulting in excellent power supply rejection ratio.

The device is qualified to meet the JEDEC standard for Pb-Free assembly and compliant to the RoHS directive.

**Electrical Performance**

Parameter	Min	Typ	Max	Units
<b>General</b>				
Output Frequency	4		39	MHz
Operating Temperature	-10/+70 -40/+85 -40/+105 -40/+125			°C
Stability Over Temperature	±50 ±25 ±20			ppm
Start Up Time			10	ms
Package Size	5.0 x 3.2 x 1.3			mm
<b>Supply</b>				
Supply Voltage (Vdd)	1.71	1.8	1.89	V
Supply Current		2	3	mA
Current, Output Disabled		0.5	1	mA
<b>Tuning</b>				
Absolute Pull Range		±25		ppm
Control Voltage to reach Pull Range	0		Vdd + 1.0	V
Control Voltage Impedance	5			MΩ
Control Voltage Modulation BW	15	20		kHz
<b>Output</b>				
Output Signal		CMOS		
Output Logic Level				
Output Level - Logic High	Vdd-0.4			V
Output Level - Logic Low			0.4	V
Output Load		15 pF		
Output Rise and Fall Time		5.0	9.0	ns
Duty Cycle	45		55	%
<b>Enable / Disable</b>				
Output Enable / Disable				
Output Enabled	Vdd x 0.7			V
Output Disabled			Vdd x 0.3	V
<b>Phase Noise &amp; Jitter</b>				
Phase Noise: ( 27MHz)				
10 Hz offset		-76		dBc/Hz
100 Hz offset		-110		dBc/Hz
1kHz offset		-123		dBc/Hz
10kHz offset		-134		dBc/Hz
100kHz offset		-138		dBc/Hz
1MHz offset		-149		dBc/Hz
10MHz offset		-154		dBc/Hz
Jitter				
RMS Jitter: (12kHz - 20MHz) - 27MHz		0.7		ps

**Notes:**

- 1 Pull Range tested with Vc = 0V to 3.0V
- 2 Rise and Fall times measured from 20% to 80% of a full output swing
- 3 Power Supply pin should be filtered. e.g. 0.1µF or 0.01 µF Capacitor for optimal performance.
- 4 The Output is Enabled if the Enable/Disable is left open.

**Maximum Ratings**



Storage Temp	-55°C to 125°C
Supply Voltage	-0.5V to +7.0V
Control Voltage	-0.5V to Vdd+0.5V
Enable/Disable Voltage	-0.5V to Vdd+0.5V
Junction Temperature	+150 °C

**Maximum Ratings Notes:**


- 1 Stresses in excess of the absolute maximum ratings can permanently damage the device.
- 2 Exposure to absolute maximum ratings for extended periods may adversely affect device reliability.

**Package Information**

Pin #	Function
Pin 1	Vc = Control Voltage or NC
Pin 2	E/D = Enable / Disable or NC
Pin 3	GND = Ground
Pin 4	OUT = Output
Pin 5	E/D = Enable / Disable
Pin 6	Vdd = Supply Voltage

**Pad Layout**

**Package Outline Drawing**
**Handling and Construction**

Package Construction	Hermetic Ceramic
Contact Pads	Gold over Nickle
Moisture Sensivity Level	MSL 1
ESD, Human Body Model	500V
ESD, Charge Device Model	500V

**Ordering Information**
**MV-VC115-5032G - E x x E x - xxMxxxxx**


① ② ③ ④ ⑤

① Voltage

E: 1.8 V

② Temp Range

J: -10/+70 °C

K: -40/+85 °C

L: -40/+105 °C

③ Temp Stability

C: ±50 ppm

E: ±25 ppm

F: ±20 ppm

④ Absolute Pull Range ⑤ Enable

E: ±25 ppm

2: Enable on Pin 2

5: Enable on Pin 5