

MV-VP210-5032G is a Voltage Controlled Crystal Oscillator (VCXO) . This VCXO provide low phase noise and jitter performance over a wide operating temperature range, LV-PECL output and comes in a Hermetic Ceramic 5.0x3.2mm package.

The device is qualified to meet the JEDEC standard for Pb-Free assembly and compliant to the RoHS directive.

**Electrical Performance**

Parameter	Min	Typ	Max	Units
<b>General</b>				
Output Frequency	60		170	MHz
Operating Temperature		-10/+70 -40/+85		°C
Stability Over Temperature		±50 ±25 ±20		ppm
Start Up Time			10	ms
Package Size		5.0 x 3.2 x 1.3		mm
<b>Supply</b>				
Supply Voltage (Vdd)	3.14	3.3	3.47	V
Supply Current		71	96	mA
Current, Output Disabled		1.2	2.5	mA
<b>Tuning</b>				
Absolute Pull Range		±50		ppm
Control Voltage to reach Pull Range	0		Vdd	V
Control Voltage Impedance	10			MΩ
Control Voltage Modulation BW	20	40		kHz
<b>Output</b>				
Output Signal		LV-PECL		
Output Logic Level				
Output Level - Logic High	2.215	2.323	2.420	V
Output Level - Logic Low	1.490	1.605	1.75	V
Output Load		50 Ω into Vdd-2V		
Output Rise and Fall Time		0.3	1.0	ns
Duty Cycle	45	50	55	%
<b>Enable / Disable</b>				
Output Enable / Disable				
Output Enabled	Vdd x 0.7			V
Output Disabled			Vdd x 0.3	V
<b>Phase Noise &amp; Jitter</b>				
Phase Noise: (122.88 MHz)				
10 Hz offset		-60		dBc/Hz
100 Hz offset		-88		dBc/Hz
1kHz offset		-118		dBc/Hz
10kHz offset		-131		dBc/Hz
100kHz offset		-145		dBc/Hz
1MHz offset		-147		dBc/Hz
10MHz offset		-147		dBc/Hz
Jitter				
RMS Jitter: (12kHz - 20MHz) - 122.88 MHz		0.3		ps

**Notes:**

- 1 Pull Range tested with Vc = 0V to 3.0V
- 2 Rise and Fall times measured from 20% to 80% of a full output swing
- 3 Power Supply pin should be filtered. e.g. 0.1μF or 0.01 μF Capacitor for optimal performance.
- 4 The Output is Enabled if the Enable/Disable is left open.

**Maximum Ratings**



Storage Temp	-55°C to 125°C
Supply Voltage	-0.3V to +5.0V
Control Voltage	-0.3V to Vdd+0.3V
Enable/Disable Voltage	-0.3V to Vdd+0.3V
Junction Temperature	+125 °C

**Maximum Ratings Notes:**

- 1 Stresses in excess of the absolute maximum ratings can permanently damage the device.
- 2 Exposure to absolute maximum ratings for extended periods may adversely affect device reliability.

**Package Information**

Pin #	Function
Pin 1	Vc = Control Voltage or NC
Pin 2	E/D = Enable / Disable
Pin 3	GND = Ground
Pin 4	OUT = Output
Pin 5	C-OUT = Complimentary Output
Pin 6	Vdd = Supply Voltage

**Pad Layout**

**Package Outline Drawing**
**Handling and Construction**

Package Construction	Hermetic Ceramic
Contact Pads	Gold over Nickle
Moisture Sensivity Level	MSL 1
ESD, Human Body Model	500V
ESD, Charge Device Model	500V

Ordering Information

MV-VP210-5032G - B x x C x - xxMxxxxx



① Voltage

B: 3.3 V

② Temp Range

J: -10/+70 °C

K: -40/+85 °C

③ Temp Stability

C: ±50 ppm

E: ±25 ppm

F: ±20 ppm

④ Absolute Pull Range ⑤ Enable

C: ±50 ppm

O: No Enable Disable

H: Enable High

L: Enable Low

**Part Number Configuration Notes:**

- Temp Range of -40 to +105 °C available in some cases