

MV-XD320-7050G is a Crystal Oscillator (XO) . This XO provides low jitter performance, LVDS output and comes in a Hermetic Ceramic 7.0x5.0mm package. This device contains an internal voltage regulator resulting in excellent power supply rejection ratio.

The device is qualified to meet the JEDEC standard for Pb-Free assembly and compliant to the RoHS directive.

## Electrical Performance

Parameter	Min	Typ	Max	Units
<b>General</b>				
Output Frequency	6.25		220	MHz
Operating Temperature	-10/+70 -40/+85 -40/+105 -40/+125			°C
Stability Over Temperature	±100 ±50 ±25 ±20			ppm
Start Up Time			10	ms
Package Size	7.0 x 5.0 x 1.7			mm
<b>Supply</b>				
Supply Voltage (Vdd)	3.14	3.3	3.47	V
Supply Current				
<100 MHZ		38	47	mA
>100 MHZ		48	60	mA
Supply Voltage (Vdd)	2.38	2.5	2.63	V
Supply Current				
<100 MHZ		34	42	mA
>100 MHZ		44	56	mA
Current, Output Disabled			30	µA
<b>Output</b>				
Output Signal		LVDS		
Output Logic Level				
Output Level - Logic High		1.43	1.60	V
Output Level - Logic Low	0.90	1.10		V
Output Load		100 Ω		
Output Rise and Fall Time		0.25	0.5	ns
Duty Cycle	45		55	%
<b>Enable / Disable</b>				
Output Enable / Disable				
Output Enabled	Vdd x 0.7			V
Output Disabled			Vdd x 0.3	V
<b>Phase Noise &amp; Jitter</b>				
Phase Noise: (156.25 MHz)				
10 Hz offset		-70		dBc/Hz
100 Hz offset		-105		dBc/Hz
1kHz offset		-131		dBc/Hz
10kHz offset		-146		dBc/Hz
100kHz offset		-152		dBc/Hz
1MHz offset		-155		dBc/Hz
10MHz offset		-156		dBc/Hz
Jitter				
RMS Jitter: (12kHz - 20MHz) - 156.25 MHz		0.1		ps

### Notes:

- 1 Stability includes initial accuracy, operating temperature, supply voltage, shock and vibration (not under operation) and aging
- 2 Rise and Fall times measured from 20% to 80% of a full output swing
- 3 Power Supply pin should be filtered. e.g. 0.1µF or 0.01 µF Capacitor for optimal performance.
- 4 The Output is Enabled if the Enable/Disable is left open.

**Maximum Ratings**


Storage Temp	-55°C to 150°C
Supply Voltage	-0.3V to +4.0V
Enable/Disable Voltage	-0.3V to Vdd+0.3V
Junction Temperature	+150 °C

**Maximum Ratings Notes:**

- 1 Stresses in excess of the absolute maximum ratings can permanently damage the device.
- 2 Exposure to absolute maximum ratings for extended periods may adversely affect device reliability.

**Package Information**

Pin #	Function
Pin 1	E/D = Enable / Disable or NC
Pin 2	E/D = Enable / Disable or NC
Pin 3	GND = Ground
Pin 4	OUT = Output
Pin 5	C-OUT = Complimentary Output
Pin 6	Vdd = Supply Voltage


**Handling and Construction**

Package Construction	Hermetic Ceramic
Contact Pads	Gold over Nickle
Pad Metal Thickness	Gold (0.3µm min - 1.0µm max) over Nickel
Moisture Sensitivity Level	MSL 1
ESD, Human Body Model	1500V
ESD, Charge Device Model	1500V

Ordering Information

**MV-XD320-7050G -**

**X X X X**

**- xxMxxxxx**

XO, LVDS

① ② ③ ④

Frequency

7.0 x 5.0 x 1.7mm, 6 Pins

**① Voltage**

B: 3.3 V  
D: 2.5 V

**② Temp Range**

J: -10/+70 °C  
K: -40/+85 °C  
L: -40/+105 °C

**③ Temp Stability**

A: ±100 ppm  
C: ±50 ppm  
E: ±25 ppm  
F: ±20 ppm

**④ Enable**

1: Enable on Pin 1  
2: Enable on Pin 2