

MV-XD530-5032G is a Crystal Oscillator (XO) . This XO provides low jitter performance, LVDS output and comes in a Hermetic Ceramic 5.0x3.2mm package. This device contains an internal voltage regulator resulting in excellent power supply rejection ratio.

The device is qualified to meet the JEDEC standard for Pb-Free assembly and compliant to the RoHS directive.

**Electrical Performance**

Parameter	Min	Typ	Max	Units
<b>General</b>				
Output Frequency	10		250	MHz
Operating Temperature		-10/+70 -40/+85		°C
Stability Over Temperature		±100 ±50 ±25 ±20		ppm
Start Up Time			10	ms
Package Size		5.0 x 3.2 x 1.3		mm
<b>Supply</b>				
Supply Voltage (Vdd)		3.3 2.5		V
Supply Current		28		mA
Current, Output Disabled		16		mA
<b>Output</b>				
Output Signal		LVDS		
Output Logic Level				
Output Level - Logic High		1.43	1.60	V
Output Level - Logic Low	0.90	1.10		V
Output Load		100 Ω		
Output Rise and Fall Time	0.125	0.350	0.500	ns
Duty Cycle	45		55	%
<b>Enable / Disable</b>				
Output Enable / Disable				
Output Enabled	Vdd x 0.7			V
Output Disabled			Vdd x 0.3	V
<b>Phase Noise &amp; Jitter</b>				
Phase Noise: (212.5 MHz)				
10 Hz offset		-39		dBc/Hz
100 Hz offset		-79		dBc/Hz
1kHz offset		-107		dBc/Hz
10kHz offset		-119		dBc/Hz
100kHz offset		-123		dBc/Hz
1MHz offset		-133		dBc/Hz
10MHz offset		-155		dBc/Hz
Jitter				
RMS Jitter: (12kHz - 20MHz) - 212.5 MHz		0.6		ps

**Notes:**

- 1 Stability includes initial accuracy, operating temperature, supply voltage, shock and vibration (not under operation) and aging
- 2 Rise and Fall times measured from 20% to 80% of a full output swing
- 3 Power Supply pin should be filtered. e.g. 0.1µF or 0.01 µF Capacitor for optimal performance.
- 4 The Output is Enabled if the Enable/Disable is left open.

**Maximum Ratings**



Storage Temp	-55°C to 125°C
Supply Voltage	4.2
Enable/Disable Voltage	-0.5 to Vdd +0.5
Junction Temperature	+125 °C

**Maximum Ratings Notes:**

- 1 Stresses in excess of the absolute maximum ratings can permanently damage the device.
- 2 Exposure to absolute maximum ratings for extended periods may adversely affect device reliability.

**Package Information**

Pin #	Function
Pin 1	E/D = Enable / Disable or NC
Pin 2	E/D = Enable / Disable or NC
Pin 3	GND = Ground
Pin 4	OUT = Output
Pin 5	C-OUT = Complimentary Output
Pin 6	Vdd = Supply Voltage

**Pad Layout**

**Package Outline Drawing**
**Handling and Construction**

Package Construction	Hermetic Ceramic
Contact Pads	Gold over Nickle
Moisture Sensivity Level	MSL 1
ESD, Human Body Model	500V
ESD, Charge Device Model	500V

**Ordering Information**
**MV-XD530-5032G -**
**X X X X**
**- xxMxxxxx**

XO, LVDS

Frequency

5.0 x 3.2 x 1.3mm, 6 Pins

① ② ③ ④

① Voltage

 B: 3.3 V  
 D: 2.5 V

② Temp Range

 J: -10/+70 °C  
 K: -40/+85 °C

③ Temp Stability

 A: ±100 ppm  
 C: ±50 ppm  
 E: ±25 ppm  
 F: ±20 ppm

④ Enable

 1: Enable on Pin 1  
 2: Enable on Pin 2