

MV-XS284-2113C is a Crystal Oscillator (XO) . This XO provides low jitter performance, SINE output and comes in a 4pin Dip, Through Hole 20.7x13.1mm package. This device contains an internal voltage regulator resulting in excellent power supply rejection ratio.

The device is qualified to meet the JEDEC standard for Pb-Free assembly and compliant to the RoHS directive.

Electrical Performance

Parameter	Min	Typ	Max	Units
General				
Output Frequency	1		600	MHz
Operating Temperature		-10/+70 to -40/+85		°C
Frequency Stability				
Stability Over Temperature		±50 to ±10		ppm
Aging (Initial 1st year)			±3	ppm
Start Up Time			5	ms
Package Size		20.7 x 13.1 x 5.1		mm
Supply				
Supply Voltage (Vdd)		+3.3 to +5.0		V
Supply Current				
1 MHz		15		mA
600 MHz		60		mA
Output				
Output Signal		SINE		
Output Logic Level				
Output Level (@+5V)		+5		dBm
Output Level (@+3.3V)	+0			dBm
Output Load		50 Ω		
Output Rise and Fall Time				
Duty Cycle				%
Enable / Disable				
Output Enable / Disable				
Output Enabled	Vdd x 0.7			V
Output Disabled			Vdd x 0.3	V
Phase Noise & Jitter				
Phase Noise: (125 MHz)				
Jitter				
RMS Jitter: (12kHz - 20MHz) - 125 MHz		1.0		ps

Maximum Ratings


Storage Temp	-55°C to 125°C
Supply Voltage	0V to +5.5V
Enable/Disable Voltage	-0.5 to Vdd +0.5
Junction Temperature	+125 °C

Maximum Ratings Notes:

- 1 Stresses in excess of the absolute maximum ratings can permanently damage the device.
- 2 Exposure to absolute maximum ratings for extended periods may adversely affect device reliability.

Package Information

Pin #	Function
Pin 1	E/D = Enable / Disable or NC (Tri-State)
Pin 2	GND = Ground
Pin 3	OUT = Output
Pin 4	Vdd = Supply Voltage



Package Outline Drawing

Handling and Construction

Package Construction	4pin Dip, Through Hole
Moisture Sensitivity Level	MSL 1
ESD, Human Body Model	500V
ESD, Charge Device Model	500V

Ordering Information
MV-XS284-2113C -

XO, SINE

20.7 x 13.1 x 5.1mm, 4 Pins

x x x 1

① ② ③ ④

- xxxMxxxx

Frequency

① Voltage

A: 5.0 V

B: 3.3 V

② Temp Range

J: -10/+70 °C

H: -20/+70 °C

K: -40/+85 °C

③ Temp Stability

C: ±50 ppm

E: ±25 ppm

F: ±20 ppm

G: ±15 ppm

J: ±10 ppm

④ Enable

1: Enable on Pin 1